## CONFIGURATION GUIDE

# N9320B RF Spectrum Analyzer

	кеузіднт 14:38:05 03-19-2018	Mkr1 2.400017GHz	Save				
	8.76dBm Atten 28dB	-21.57dBm	Save Now	Span	View/ Trace	Det/ Display	Aarker
Log 10 /div		Passed		Amplitude	Mode	Meas	Aarker
/810			Type⊁ Screen				-
	-21.24dBm				3 9		
	-31.24dBn						
				4 !	5 6		
HI P						-	
S3 P	1 the 20 the set white the stand	A. L. Jack & Hickory Sugar			2 3	Bk Sp	
	A MARK A ANALADA LAAAAAU		Hane		+/_	Enter	
mote Swee FC						Litter	
				TG Source	Cal Output 50 MHz- 10 dBm	Probe	RF Input
		Span 5.000MHz Sweep 20.04ms	Return		6		
Cent RBW	30.00kHz VBW 30.00kHz	3086p 20.04#5					
Cent	30.00kHz VBW 30.00kHz	Sileep 2010485			0	e	
FC tandby	-81.24dBn	Span 5.000MHz	Return	TG Source			RI



# Configure Your Keysight N9320B RF Spectrum Analyzer

The Keysight Technologies, Inc. N9320B is a general purpose spectrum analyzer from 9 kHz to 3 GHz. Its standard features include:

- Frequency power measurements
- One-button power suite, auto tune, and frequency counter
- AM/FM tune and listen
- 12 markers, 4 traces, and 2 customer-definable limit lines
- U2000 Series USB power sensor support
- USB and LAN connectivity

This step-by-step process will help you to configure your N9320B RF spectrum analyzer by tailoring its options to meet your requirements.

For detailed specifications, refer to the N9320B spectrum analyzer data sheet (5990-8119EN). For a product overview, refer to the N9320B spectrum analyzer brochure (5990-8118EN).

## Ordering information

Description	Model number	Additional information
RF spectrum analyzer, 9 kHz to 3.0 GHz	N9320B	Accessories supplied as standard with each analyzer: Quick Start Guide, USB cable, N-BNC adapter, BNC cable, power cord, and documentation CD-ROM
Description	Option number	Additional information
Step 1. Add a preamplifier		
Preamplifier, 3.0 GHz	N9320B-PA3	Preamplifier improves the noise floor for low-level signal detection
Step 2. Add modulation analysis capability		
AM and FM demodulation metrics	N9320B-AMA	Provides modulation metrics of an AM or FM signal: Carrier power, modulation rate, AM depth, frequency deviation, SINAD <sup>1</sup> , and carrier frequency offset
ASK and FSK demodulation metrics	N9320B-DMA	Provides modulation metrics of an ASK or FSK signal: Carrier power, ASK error, depth, and index, FSK deviation, FSK error, magnitude error, and carrier frequency offset
Step 3. Add scalar stimulus-response measure	ment capability	
Tracking generator, 100 kHz to 3.0 GHz	N9320B-TG3	A cost-effective method to measure transmission characters of RF devices. An external bridge or a directional coupler needs to be added to implement reflection measurements
Step 4. Add optional features		
Resolution bandwidth (–6 dB): 200 Hz, 9 kHz, 120 kHz, and 1 MHz	N9320B-EMF	Provides optional CISPR16-1-1 EMI filters for preliminary EMI pre-compliance measurements
GPIB interface	N9320B-G01	IEEE-488 bus connector, used in test automation systems
Customized save-last utility	N9320B-C20	N9320B automatically saves its settings and status once any changes are made. After the power cycle, the N9320B recovers the prior setups before powering off
Instrument power-on utility at AC power cycle	N9320B-C30	N9320B powers on directly at AC power cycle without the user pushing the power-on button on the unit's front panel. A solution designed for test automation systems. Only orderable along with the base instrument

1. Signal-to-noise and distortion ratio.

# Configure Your Keysight N9320B RF Spectrum Analyzer (Continued)

Description	Option number	Additional information
Step 5. Add optional accessories		
RF training kit	Y1800A	Consists of RF transceiver and a full set of pre-written lab sheets. Prepared for RF teaching labs or training agencies
Hard transit case (D x W x H)	N9320B-1TC	645 x 444 x 268 mm, 13 kg nominal
		25.4 x 17.5 x 10.6 in, 29 lb nominal
Rack mount kit	N9320B-1CM	Includes a rackmount flange and front handle kit. Fits standard 19-inch rack and occupies three units of rack space

Need more RF and microwave accessories? Visit www.keysight.com/find/accessories.

Description	Option number	Additional information
Step 6. Choose localized User's Guide		
English User's Guide	N9320B-ABA	
Simplified Chinese User's Guide	N9320B-AB2	
Japanese User's Guide	N9320B-ABJ	
Step 7. Add calibration, technical training, supp	ort, and upgrade	
Commercial calibration certificate with test data	N9320B-UK6	Calibration certificate only available at time of instrument purchase; only provides measurement results
Select Keysight Calibration Plan		
<ul> <li>3-year calibration assurance plan (return to Keysight)</li> </ul>	R-50C-011-3	Priority calibration service covering all calibration costs for 3 years; 15% cheaper than buying stand-alone calibrations
<ul> <li>5-year calibration assurance plan (return to Keysight)</li> </ul>	R-50C-011-5	Priority calibration service covering all calibration costs for 5 years; 20% cheaper than buying stand-alone calibrations

Other calibration options may available, for more information on calibration, go to: www.keysight.com/find/calibration. For more information on training and application support services, go to: www.keysight.com/find/training.

# Instrument Upgrades

Most of the Keysight N9320B RF spectrum analyzer options are available for post-sales retrofit.

For license-key upgrades that do not require additional hardware:

- 1. Place an order for the upgrade with Keysight and request to receive the software entitlement certificate through email
- 2. Install the license key in the N9320B. Upgrade firmware to the latest revision if required
- 3. Restart the N9320B
- 4. Begin using the new capability

-PA3	
AIVIA	
-DMA	
-TG3 The tracking	g generator is additional hardware that is installed inside the
N9320B. Up	pgrade is performed at Keysight's local service center
-G01 Requires ad	ditional hardware be installed inside the N9320B
-EMF	
-1TC	
-1CM	
-C20	
-R2C Enables the	e latest feature set for the instrument
3K 3K 3K 3K 3K	N9320B. U           3K-G01         Requires ad           3K-EMF         3K-1TC           3K-1CM         3K-220

A comprehensive summary about the N9320B upgrades is also available at: www.keysight.com/find/n9320b\_upgrade.

## **Related Literature**

Publication title	Publication number
N9310A RF Signal Generator - Data Sheet	5990-8116EN

# Other Information

#### Keysight product registration

Register your instruments for service notifications, firmware update alerts, application notes and more. You have the Keysight edge. Register today and keep it sharp: www.keysight.com/find/register.

#### Keysight education corner

Your one-stop education resource for college and university engineering educators, researchers and students: www.keysight.com/find/edu.

## Learn more at: www.keysight.com

For more information on Keysight Technologies' products, applications or services, please contact your local Keysight office. The complete list is available at: www.keysight.com/find/contactus

